



APPLICATIONS

Eni Sport 10W-60 is a latest generation lubricant, developed to meet the lubrication requirements of high performance engines. It is a lubricant with top synthetic technology suitable for engines that operate in extreme conditions such as competition engines with high specific powers, driving conditions (eg rallying), off-road engines operating at high temperatures (desert).

CUSTOMER ADVANTAGES

- The synthetic components used in the formulation guarantee a perfect adherence to metal surfaces even for prolonged engine stopping periods, facilitating the start-up phases and ensuring greater protection and reduction of the effects linked to wear phenomena.
- The viscosimetric characteristics of the product guarantee excellent lubrication of the mechanical components of the engine in any operating condition and temperature, even after prolonged periods of use.
- The particular selection of the components used in the formulation considerably reduces the effects linked to the volatility and at the same time allows a high thermal stability.

SPECIFICATIONS - APPROVALS

- API SL





CHARACTERISTICS

| Properties | Method | Unit | Typical |
|--------------------|-------------|--------------------|---------|
| Density at 15°C | ASTM D 4052 | kg/m ³ | 856 |
| Viscosity at 100°C | ASTM D 445 | mm ² /s | 23.4 |
| Viscosity at 40°C | ASTM D 445 | mm ² /s | 165 |
| Viscosity Index | ASTM D 2270 | - | 172 |
| Viscosity at -25°C | ASTM D 5293 | mPa·s | 6800 |
| Pour point | ASTM D 97 | °C | -27 |

