



APPLICATIONS

Eni Rotra ATF III is a lubricant for automatic transmissions and power steering gears, specifically formulated to comply with the most demanding specifications of the main American and European OEMs.

CUSTOMER ADVANTAGES

- **Eni Rotra ATF III** has an excellent oxidation stability, preventing deterioration of lubricant from high temperature operations, and the formation of sludge.
- A balanced set of friction modifiers provides a outstanding transmission efficiency and smooth, silent gear shifting.
- **Eni Rotra ATF III** ensures a complete compatibility with a wide range of elastomers and metal alloys, very good cold properties and high antiwear properties for all contact surfaces.

SPECIFICATIONS - APPROVALS

- GM DEXRON III G
- MB 236.6
- Ford MERCON
- MAN 339 type L - 1
- MAN 339 type Z - 1
- MAN 339 type V - 1
- ZF TE-ML 04D, 05L, 09, 14A, 21L
- Allison C-4
- Volvo 97340
- Voith H55.6335.xx





CHARACTERISTICS

Properties	Method	Unit	Typical
Colour		-	red
Density at 15°C	ASTM D 4052	kg/m ³	850
Viscosity at 100°C	ASTM D 445	mm ² /s	7.35
Viscosity at -40°C	ASTM D 2983	mPa·s	18000
Viscosity at 40°C	ASTM D 445	mm ² /s	36
Viscosity Index	ASTM D 2270	-	170
Flash point (COC)	ASTM D 92	°C	210
Pour point	ASTM D 97	°C	-45

